

FlatClient PRO RPL

Industrial Panel PC



All-in-one Panel PC for Visualization and Control on Machines, Devices and Plants

- Robust design with metal housing and tempered front lens
- Anti-glare and anti-fingerprint PCAP multitouch provides excellent readability and operability
- Display sizes from 10.1" to 23.8" with WXGA/Full-HD resolution for brilliant visualization
- Flexible compute performance with 13th Gen Intel® Core™ processors
- Ready for application software or integrated web panel functionality

	FEATURES	FLATCLIENT PRO RPL
DISPLAY	SIZE/RESOLUTION BRIGHTNESS VIEWING ANGLE BACKLIGHT	10.1", 12.1": 1280x800 15.6", 18.5", 21.5", 23.8": 1920x1080 See table below for more details See table below H170°/V170° or better (see table below) Life time ≥ 50.000 h
TOUCH	TOUCHSCREEN FRONT LENS	Projected capacitive touch (PCAP); 10-finger multitouch Resistive touch* Tempered glass, anti-fingerprint, anti-glare, edge protected
PROCESSOR / MEMEORY / STORAGE	PROCESSOR RAM STORAGE	Intel® U300E (5C, 1.1/4.3 GHz, up to 28W) Intel® Core™ i3-1315UE (6C, 1.2/4.5 GHz, up to 28W) Intel® Core™ i5-1345UE (10C, 1.4/4.6 GHz, up to 28W) Intel® Core™ i7-1365UE (10C, 1.7/4.9 GHz, up to 28W) 8/16/32/64 GByte DDR5 128 ... 1024 GByte (m.2 SATA)
INTERFACES	STANDARD INTERFACES OPTIONAL INTERFACES* CONTROLS POWER IN	2x 2.5 GbE 4x USB 3.2 Gen 2 (Type A Connector) 2x DP RS232, Audio Line-out, Speaker out (2W), WiFi 6, Bluetooth, RFID PWR switch, USB 3.0 (part of IO shield) 24V DC (14-32V DC)
SOFTWARE SUPPORT	OPERATING SYSTEM WEB PANEL	Win10 IoT Enterprise, Win 11 IoT Enterprise, Linux (Debian), Kontron OS** QIWI***
MECHANICAL	HOUSING MOUNTING COOLING	Metal housing, Powder coated (VESA) or zinc plated (panel mount) Panel mount (built-in), VESA 75/100 (stand-alone) Fanless, passive cooling
ENVIRONMENTAL	OPERATING TEMPERATRUE STORAGE TEMPERATURE PROTECTION CLASS HUMIDITY ALTITUDE SHOCK VIBRATION MTBF	0 °C to +50 °C -20°C to +70 °C Front: IP65, rear IP20 10 %-90 % @ 39 °C, non condensing Up to 3.000m (10.000 ft) 15 G 11 ms duration (half sine; ACC. TO EN 60068-2-27) 10-500 Hz: 1G/3 axis (ACC. TO EN 60068-2-6) >50.000h
APPROVALS	CERTIFICATIONS	CE, UL, CB

*Configuration Option

**Hardened and secure Linux®-based KontronOS operating system/on request

***QIWI-Toolkit: For web panel operation

Display Information

DISPLAY SIZE	RESOLUTION	FORMAT	BRIGHTNESS	DIMENSIONS	VIEWING ANGLE	COLORS	WEIGHT
10.1"	1280x800	16:10	500cd	276 x 195 x 65	H170 ° / V170 °	16.2 million	~ 3,7 kg
12.1"	1280x800, WXGA	16:10	500cd	315 x 228 x 65	H178 ° / V178 °	16.7 million	~ 4,7 kg
15.6"	1920x1080, Full HD	16:9	450cd	399 x 260 x 74	H178 ° / V178°	16.7 million	~ 6,5 kg
21.5"	1920x1080, Full HD	16:9	300cd	533 x 339 x 74	H178 ° / V178 °	16.7 million	~ 10,5 kg
23.8"	1920x1080, Full HD	16:9	250cd	591 x 361 x 69	H178 ° / V178 °	16.7 million	~ 11,8 kg

Global Headquarters

Kontron Europe GmbH

Gutenbergstraße 2
 85737 Ismaning, Germany
 Tel.: + 49 821 4086-0
 info@kontron.com

www.kontron.com

